

RECostal® SF

2024.02_01_EN



RECostal® SF are coiled formwork units designed to install openings win structural and civil engineering.

Main Characteristics

- Strong bond to concrete
- Many sizes possible due to pre-punching profiling at distance of 5 cm
- Easy vertical bending
- Various shape possible

Technical Data

- Material: profiled, pre-punching sheet steel
- Thickness mesh: 0,7 mm
- Packaging: packed on pallets, 10 m rolls

TYPE	HEIGHT H [m]	LENGTH L [m]	QUANTITY [m/pal.]
SF 14	14	10	480
SF 16	16	10	480
SF 18	18	10	420
SF 20	20	10	360
SF 22	22	10	360
SF 24	24	10	300
SF 26	26	10	300
SF 28	28	10	300
SF 30	30	10	300

Installation

Unroll the SF tape to the required length and cut to size with metal shears or timmer. Create needed shape and join the overlaps of SF tape using tie wire. Place the finished opening form in the planned structure and secure into position, as well as stiffening.

Safety/ Recommendations*

Wear protective gloves.

*The recommendations relating to the application and end-use of our products are based on our current knowledge and experience of the products when properly stored, handled and applied under normal conditions. No warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any other advice offered. The user shall rely on his or her own information and tests to determine suitability of the product for the intended use. We reserve the right to update information due to technical progress.